



JKL PART NUMBER	- A - LENGTH	COLOR 5000 °k	STARTING CIRCUIT VOLTAGE VS (Vrms) @ 0°C	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mArms)	BRIGHTNESS (CANDELA/m2)	*RATED LIFE (HRS)
CF26346-37B	346 ± 3.0	x = $.345 \pm .01$ y = $.360 \pm .01$	1450	700	6 ± 1	36,000 ± 15%	40,000
CF26397-37B	397 ± 3.0		1520	725			
CF26448-37B	448 ± 3.0		1820	870			
CF26499-37B	499 ± 3.0		2100	1000			
CF26550-37B	550 ± 3.0		2270	1100			
CF26600-37B	600 ± 3.0		2340	1125			

*NOTE: RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0.20 ANGLE +/- 0		JKL COMPONENTS CORPORATION			
DRAWN BY L. WENGSTROM		APPV'D BY DATE J.K. 11/18/04		SIZE A	FSCM NO. 55335	DRAWING NO. CF 26-37B	
TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP		- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE	RELEASED DATE 11/17/04	REVISION DATE 11/18/04	
REV. NO.	DESCRIPTION/ECO NUMBER	APPV'D DATE	REV. NO. A	SHEET 1 OF 1			